

CLAIMS

What is claimed is:

- 5 1. A memory board for a data storage system, comprising:
 an interface which is configured to couple to a bus of the data storage
 system;
 memory which is configured to store a doubly linked list data structure;
 and
10 a memory board control circuit, coupled to the interface and the memory,
 the memory board control circuit being configured to:
 receive a modify command from a processor of a
 data storage system through the interface, the processor
 being configured to move data within the data storage
15 system,
 atomically modify the doubly linked list data
 structure in accordance with the modify command, and
 provide a result to the processor of the data storage
 system through the interface in response to modifying the
20 doubly linked list data structure.
2. The memory board of claim 1 wherein the doubly linked list data structure is a
doubly linked list shared data structure.

3. The memory board of claim 2 wherein the doubly linked list shared data structure includes multiple entries, wherein the modify command is a remove instruction, and wherein the memory board control circuit is configured to atomically modify the doubly linked list shared data structure by removing an entry from the doubly linked list shared data structure in response to the remove instruction.
- 5
4. The memory board of claim 2 wherein the doubly linked list shared data structure includes multiple entries, wherein the modify command is an add instruction, and wherein the memory board control circuit is configured to atomically modify the doubly linked list shared data structure by adding an entry to the doubly linked list shared data structure in response to the add instruction.
- 10
5. The memory board of claim 2 wherein the doubly linked list shared data structure includes multiple entries, wherein the modify command is a move instruction, and wherein the memory board control circuit is configured to atomically modify the doubly linked list shared data structure by moving an entry from a first position in the doubly linked list shared data structure to a second position in the doubly linked list shared data structure in response to the move instruction.
- 15
6. The memory board of claim 2 wherein the memory board control circuit is configured to atomically modify the doubly linked list shared data structure by performing a series of individual transactions on the doubly linked list shared data structure, and wherein the memory board control circuit is configured to provide, as the result, a series of transaction outputs respectively corresponding to the series of individual transactions.
- 20
- 25

7. A data storage system, comprising:
- a set of storage devices;
 - a processor which is configured to move data to and from the set of storage devices;
 - 5 a bus coupled to the processor; and
 - a memory board that includes (i) an interface which couples to the bus, (ii) memory which is configured to store a doubly linked list data structure, and (iii) a memory board control circuit, coupled to the interface and the memory, the memory board control circuit being configured to:
- 10 receive a modify command from the processor of the data storage system through the interface and the bus, atomically modify the doubly linked list data structure in accordance with the modify command, and provide a result to the processor of the data storage
- 15 system through the interface and the bus in response to modifying the doubly linked list data structure.
8. The data storage system of claim 7 wherein the doubly linked list data structure is a doubly linked list shared data structure.
- 20
9. The data storage system of claim 8 wherein the doubly linked list shared data structure includes multiple entries, wherein the modify command is a remove instruction, and wherein the memory board control circuit is configured to atomically modify the doubly linked list shared data structure by removing an
- 25 entry from the doubly linked list shared data structure in response to the remove instruction.

10. The data storage system of claim 8 wherein the doubly linked list shared data structure includes multiple entries, wherein the modify command is an add instruction, and wherein the memory board control circuit is configured to atomically modify the doubly linked list shared data structure by adding an entry to the doubly linked list shared data structure in response to the add instruction.
11. The data storage system of claim 8 wherein the doubly linked list shared data structure includes multiple entries, wherein the modify command is a move instruction, and wherein the memory board control circuit is configured to atomically modify the doubly linked list shared data structure by moving an entry from a first position in the doubly linked list shared data structure to a second position in the doubly linked list shared data structure in response to the move instruction.
12. The data storage system of claim 8 wherein the memory board control circuit is configured to atomically modify the doubly linked list shared data structure by performing a series of individual transactions on the doubly linked list shared data structure, and wherein the memory board control circuit is further configured to provide, as the result, a series of transaction outputs respectively corresponding to the series of individual transactions.
13. The data storage system of claim 12 wherein the series of transaction outputs provided by the memory board control circuit includes a first transaction output and a second transaction output; wherein the processor is configured to (i) generate a pseudo transaction output based on the first transaction output and (ii) compare the pseudo transaction output to the second transaction output in order to error check operation of the memory board.

14. In a memory board of a data storage system, a method for accessing a doubly linked list data structure, the method comprising the steps of:
- receiving a modify command from a processor of a data storage system through a bus of the data storage system, the processor being configured to move data within the data storage system,
- atomically modifying the doubly linked list data structure in accordance with the modify command, and
- providing a result to the processor of the data storage system through the bus in response to modifying the doubly linked list data structure.
15. The method of claim 14 wherein the step of atomically modifying the doubly linked list data structure includes the step of:
- updating, as the doubly linked list data structure, a doubly linked list shared data structure in an atomic manner.
16. The method of claim 15 wherein the doubly linked list shared data structure includes multiple entries, wherein the modify command is a remove instruction, and wherein the step of updating the doubly linked list shared data structure includes the step of:
- removing an entry from the doubly linked list shared data structure in response to the remove instruction.

17. The method of claim 15 wherein the doubly linked list shared data structure includes multiple entries, wherein the modify command is an add instruction, and wherein the step of updating the doubly linked list shared data structure includes the step of:
- 5 adding an entry to the doubly linked list shared data structure in response to the add instruction.
18. The method of claim 15 wherein the doubly linked list shared data structure includes multiple entries, wherein the modify command is a move instruction, and
- 10 wherein the step of updating the doubly linked list shared data structure includes the step of:
- moving an entry from a first position in the doubly linked list shared data structure to a second position in the doubly linked list shared data structure in response to the move instruction.
- 15 19. The method of claim 15 wherein the step of updating the doubly linked list shared data structure includes the step of:
- performing a series of individual transactions on the doubly linked list shared data structure, and
- 20 wherein the step of providing the result includes the step of:
- outputting, as the result, a series of transaction outputs respectively corresponding to the series of individual transactions.

20. The method of claim 19 wherein the series of transaction outputs provided by the memory board control circuit includes a first transaction output and a second transaction output; and wherein the method further comprises the step of:

5 performing an error handling routine in response to an error message from the processor resulting from (i) generation of a pseudo transaction output based on the first transaction output and (ii) a comparison of the pseudo transaction output to the second transaction output in order to error check operation of the memory board.

10 21. A memory board control circuit for accessing a doubly linked list data structure of a data storage system, the memory board control circuit being mountable to a memory board, the memory board control circuit comprising:

15 an input port that couples to a bus of the data storage system;
an output port that couples to the bus of the data storage system; and
control logic, connected to the input port and to the output port, that is configured to:

20 receive a modify command from a processor of a data storage system through the input port, the processor being configured to move data within the data storage system,

25 atomically modify the doubly linked list data structure in accordance with the modify command, and
provide a result to the processor of the data storage system through the output port in response to modifying the doubly linked list data structure.

22. The memory board control circuit of claim 21 wherein the doubly linked list is a doubly linked list shared data structure.